


38 803 001 RAPID SL ELEMENT FOR URINAL WITH INFRA-RED ELECTRONIC






PRODUCT DESCRIPTION

- · with GROHE Rapido U
- 1.13 and 1.30 m installation height
- for manual actuation or Tectroninfra-red electronic 6 V or 230 V
- · for on-the-wall installations or studded walls
- powder coated steel frame, self-supporting
- for dry-cladding, completely pre-assembled
- · height adjustable fitting connections
- · quick adjustment, lockable
- · fixing material
- TÜV approved
- HT-outlet bend Ø 50 mm
- · inlet connection and inlet connecting set
- fixing bolts M8, with fixing device for ceramic
- · water group with stop valve
- flow pressure min 0.5 bar
- operating pressure max 10 bar
- flush aid
- · functional unit checked ex factory
- water supply connections 1/2" outer thread
- connecting box for mains supply 230 V
- · installation box with gasket
- shortable inspection shaft incl. protection during construction phase for sets for final installation with dimensions 116 x 144 mm
- including wall brackets 38 558 00M for on-the-wall installation



38 803 001 RAPID SL ELEMENT FOR URINAL WITH INFRA-RED ELECTRONIC



SPARE PARTS, November 2015 - now

- 1: Flush elbow 2" (Spare part-nr. 42943000)
- 1.1: holder (Spare part-nr. 42236000)
- 2: Threaded bolt (Spare part-nr. 43078000)
- 3: Fastening set (Spare part-nr. 4307500M)
- 4: Switching power supply (Spare part-nr. 42470000)
- 5: Inspection shaft (Spare part-nr. 66838000)
- 6: Isolating valve (Spare part-nr. 43392000)
- 7: Wall union (Spare part-nr. 3855800M)